

SI-211 QBEAM 90




Smaller---very compact in size and weight
Better---very high in output

The QBEAM 90 features a 7500K 90W LED with high intensity and efficiency. It produces very high light output, through a specific 3° optic system. The PAN/TILT integrates in fast and quiet movement. It offers a full complement of professional characteristics, including a static gobo wheel, color wheel, 8-facet prism, linear electronic focus, 0-100% linear LED dimmer, variable speed shutter/strobe.

The fixture is applicable for small-medium scale live concerts, DJ Shows, schools, clubs, weddings, etc.

Features

- > A 90W white LED lamp, 7500K
- > 50000 hours life span and low power consumption
- > 8/16 bit smooth and precise resolution for PAN/TILT movement
- > 540° PAN and 260° TILT movement
- > PAN/TILT inversion available
- > Scan position memory, auto reposition after unexpected movement
- > Specific high precision glass optic system with 3° projection angle
- > Improved optics and flat beam field
- > 1 Static gobo wheel with 13 gobos plus open
- > 1 Color wheel with 12 colors plus open
- > Variable direction rainbow effect with speed adjustable
- > 8-Facet prism with variable speed and direction
- > 0-100% linear LED dimmer
- > 25T/sec high speed LED shutter/strobe effect with variable speed
- > Preset variable/random strobe and dimming pulse effect
- > 10/12/15 DMX channels USITT DMX-512
- > DMX512, master-slave, and sound activated controllable or auto operation
- > 2.0" High resolution TFT LCD display with 4 light-touch control buttons
- > POWERCON connector IN/OUT
- > 3-Pin XLR connectors IN/OUT
- > High efficiency and low noise cooling system
- > -20~45°C max ambient temperature
- > IP20 protection rating
- > 55dB at 3'dB rating
- > 1*1/4 turn fastening Omega clamp
- > 1*Safety attachment point



SI-212 QBEAM 150

Specifications

Input Voltage:	AC100-240V 50/60Hz
LED Quantities:	1*150W white LED
Control Signal:	DMX512, master-slave and sound activated or auto operation
Control Channel:	10/12/15 DMX channels USITT DMX-512
Power Consumption:	215W
Dimensions:	170(D)*226(W)*362(H)mm
Packing Dimensions:	280(D)*295(W)*385(H)mm
Net Weight:	7.6kg
Gross Weight:	9.2kg

SI-211 QBEAM 90

Specifications

Input Voltage:	AC100-240V 50/60Hz
LED Quantities:	1*90W white LED
Control Signal:	DMX512, master-slave and sound activated or auto operation
Control Channel:	10/12/15 DMX channels USITT DMX-512
Power Consumption:	135W
Dimensions:	170(D)*226(W)*362(H)mm
Packing Dimensions:	280(D)*295(W)*385(H)mm
Net Weight:	7.9kg
Gross Weight:	9.6kg

SI-210 QBEAM 50

Specifications

Input Voltage:	AC100-240V 50/60Hz
LED Quantities:	1*50W white LED
Control Signal:	DMX512, master-slave and sound activated or auto operation
Control Channel:	10/12/15 DMX channels USITT DMX-512
Power Consumption:	75W
Dimensions:	170(D)*226(W)*362(H)mm
Packing Dimensions:	280(D)*295(W)*385(H)mm
Net Weight:	7.9kg
Gross Weight:	9.6kg

